## IN THE CLAIMS

Please amend the claims as follows:

Claim 1 (Currently Amended): A glass having comprising at least one type of alkali metal ion, an alkali-metal-ion concentration gradient from its surface over an exchange depth of at least 100 µm, a surface stress of at least 200 MPa and a strain point in the core of at least 550°C.

Claim 2 (Currently Amended): The glass of claim 1 as claimed in the preceding elaim, characterized in that it has wherein the glass comprises an interdiffusion coefficient, at 400°C, of the alkali metal ions exchanged, of at most 9 x 10<sup>-17</sup> m<sup>2</sup>.s<sup>-1</sup>.

Claim 3 (Currently Amended): The glass of claim 2 as claimed in one of the preceding claims, characterized in that wherein the ratio of the interdiffusion coefficient, at 490°C, of the exchanged alkali metal ions, to the interdiffusion coefficient, at 400°C, of the exchanged alkali metal ions, is at least 20:1.

Claim 4 (Currently Amended): The glass of claim 1 as claimed in one of the preceding claims, characterized in that the wherein the glass comprises an interdiffusion coefficient, at 490°C, of the exchanged alkali metal ions, [[is]] of less than 2 x 10<sup>-15</sup> m<sup>2</sup>.s<sup>-1</sup>.

Claim 5 (Currently Amended): The glass of claim 1 as claimed in one of the preceding claims, characterized in that wherein the strain point in the core is at least 570°C.

Claim 6 (Currently Amended): The glass of claim 1 as claimed in one of the preceding claims, characterized in that wherein the at least one type of alkali metal ion is

Docket No. 289351US0PCT Preliminary Amendment

selected from the group consisting of the exchange ions are chosen from Na<sup>+</sup>, Li<sup>+</sup>, K<sup>+</sup> and combinations thereof.

Claim 7 (Currently Amended): The glass of claim 1 as claimed in one of the preceding claims, characterized in that wherein the exchange depth of alkali metal ion exchange is at most 300 µm.

Claim 8 (Currently Amended): The glass of claim 1 as claimed in one of the preceding claims, characterized in that it wherein the glass meets the EN 60335-2-6 standard.

Claim 9 (Currently Amended): A pane comprising the glass of one of the preceding claims The glass of claim 1, in the form of a pane.

Claim 10 (Currently Amended): The pane of claim 9 as claimed in the preceding claim, characterized in that its wherein the thickness of the pane ranges from 2 to 7 mm.

Claim 11 (Currently Amended): The pane of claim 9 as claimed in the preceding claim, characterized in that its wherein the thickness of the pane ranges from 2.8 to 5 mm.

Claim 12 (Currently Amended): A door comprising the glass pane of claim 9 or the pane of one of the preceding claims.

Claim 13 (Currently Amended): The door of claim 12 as claimed in the preceding elaim, comprising hinges directly incorporated into said the pane.

Claim 14 (Currently Amended): The door of claim 12 as claimed in one of the preceding door claims, characterized in that wherein the border of the pane is protected by a seal.

Claim 15 (Currently Amended): A cooker or fire screen or flue insert, comprising the glass of claim 1 or the pane or the door of one of the preceding claims.

Claim 16 (Currently Amended): An oven comprising a door the door of claim 12 of one of the preceding door claims.

Claim 17 (Currently Amended): The oven of claim 16 as claimed in the preceding elaim, characterized in that it is of the wherein the oven is a pyrolytic oven type.

Claim 18 (Currently Amended): A stove comprising [[a ]] the door of claim 12 one of the preceding door claims.

Claim 19 (Currently Amended): A method of separating The use of a pane as claimed in one of the preceding pane claims for separating two gaseous atmospheres at different temperatures, the first being at a temperature ranging from 300 to 530°C and the second being at a temperature at least 50°C below the first, comprising separating the two gaseous atmospheres with the pane of claim 9.

Docket No. 289351US0PCT Preliminary Amendment

Claim 20 (Currently Amended): The <u>method of claim 19</u> use as claimed in the preceding claim, characterized in that <u>wherein</u> the second gaseous atmosphere is at a temperature at least 100°C below the first.

Claim 21 (Currently Amended): The <u>method of claim 20</u> use as claimed in the <u>preceding claim</u>, characterized in that <u>wherein</u> the second atmosphere is at room temperature.